

Total RFID Tag Solutions

Cimtrac RFID ID Card & Keyfob Tag

Size : ID Card - 85.6x54x0.8mm,
Keyfob - 36x30x7.5mm, 54x28x1.8mm
Tag IC : NXP Mifare , I-CODE & U-CODE G2X(ID Card Only)
Operating Frequency : 13.56MHz & 860~960MHz
Operating Temperature : -25°C ~ +50°C
Storage Temperature :
PVC : -25°C ~ +50°C
PETG : -25°C ~ +80°C



Cimtrac RFID Metal Tag

Size :
1.Slim : 90x40x2 mm
2.Disc : Diameter – 50mm x T 8mm
IP Class : IP68(Disc Metal Tag Only)
Tag IC : NXP UCODE G2X
Operating Frequency : 860~960MHz
Operating Temperature : -25°C ~ +50°C
Storage Temperature :
1.Slim : -25°C ~ +50°C
2.Disc : -40°C ~ +100°C



Cimtrac RFID Disc Tag

Size :
1.HF : Diameter – 35mm x T 8mm
2.UHF : Diameter – 50mm x T 8mm, Diameter – 30mm x T 3mm
Tag IC : NXP I-CODE & UCODE G2X
Operating Frequency : 13.56MHz & 860~960MHz
Operating Temperature : -25°C ~ +50°C
Storage Temperature : -25°C ~ +50°C

