

## Total RFID Tag Solutions

### Cimtrac RFID ID Card & Keyfob Tag

Size : ID Card - 85.6x54x T 0.8mm,  
Keyfob - 36x30x T 7.5mm, 54x28x T 1.8mm  
Tag IC : NXP Mifare/ I-CODE & Alien H3  
Operating Frequency : 13.56MHz & 860~960MHz  
Operating Temperature : -25°C ~ +50°C  
Storage Temperature :  
PVC : -25°C ~ +50°C  
PETG : -25°C ~ +80°C



### Cimtrac RFID Windshield Label

Size : 69x25mm  
IP Class : IP68  
Tag IC : Alien H3  
Operating Frequency : 860~960MHz  
Operating Temperature : -25°C ~ +50°C  
Storage Temperature : -25°C ~ +80°C



### Cimtrac RFID Metal Tag

Size :  
1. Mini : 39x13x T 2mm  
2. Classic : 90x40x T 2mm  
3. Disc : Diameter - 50mm x T 8mm  
IP Class : IP68  
Tag IC : Alien H3  
Operating Frequency : 860~960MHz  
Operating Temperature : -25°C ~ +50°C  
Storage Temperature : -40°C ~ +100°C



### Cimtrac RFID High temperature Tag

Size : 50x20x T 5mm  
IP Class : IP68  
Tag IC : NXP I-CODE  
Operating Frequency : 13.56MHz  
Operating Temperature : -25°C ~ +50°C  
Storage Temperature : -40°C ~ +240°C



### Cimtrac RFID Disc Tag

Size :  
1. HF : Diameter - 35mm x T 8mm ,Diameter - 50mm x T 3.5mm  
2. UHF : Diameter - 50mm x T 8mm,Diameter - 30mm x T 3mm  
Tag IC : NXP I-CODE & Alien H3  
Operating Frequency : 13.56MHz & 860~960MHz  
Operating Temperature : -25°C ~ +50°C  
Storage Temperature : -25°C ~ +50°C



**Cimtrac Systems,Inc.**

V2.0

<http://www.cimtrac.com.tw>

Tel: (886)2-27113492 Fax: (886)2-27119331

9F,No.100,,Sec 3,ZhongXiao East Rd., Taipei City 106,Taiwan,R.O.C.